

Harken Chrome Winch Range

BRIERLEY
HOSE AND HANDLING


Radial White Self Tailing

Harken Radial Line winches have successfully balanced the need for a secure grip and line longevity with smooth, controlled easing while under load. Details sailors will appreciate: smaller winches that carry higher loads, stress-free seasonal maintenance, and one-person installation with easy upgrades to power.

Patented angle of ribs drives line wraps down when easing to keep them on area of drum that provides best control.

High-strength composite roller bearings and bushings reduce friction under load. Load-carrying gears and pins are 17-4 PH stainless steel for strength, corrosion resistance.



Prod No.	Name	Speed	Base Ø (mm)	Base Ø (in)	Maximum line Ø (mm)	Maximum line Ø (in)
 20.2STCW	20 Self-Tailing Radial White Winch	1	137	5 3/8	12	1/2
 35.2STCW	35 Self-Tailing Radial White Winch — 2 Speed	2	149	5 7/8	12	1/2
 40.2STCW	40 Self-Tailing Radial White Winch — 2 Speed	2	157	6 3/16	12	1/2
 46.2STCW	46 Self-Tailing Radial White Winch — 2 Speed	2	184	7 1/4	14	9/16
 50.2STCW	50 Self-Tailing Radial White Winch — 2 Speed	2	194	7 5/8	14	9/16
 60.2STCW	60 Self-Tailing Radial White Winch — 2 Speed	2	236	9 5/16	16	5/8
 60.3STCW	60 Self-Tailing Radial White Winch — 3 Speed	3	236	9 5/16	16	5/8
 70.2STCW	70 Self-Tailing Radial White Winch — 2 Speed	2	240	9 7/16	18	11/16
 70.3STCW	70 Self-Tailing Radial White Winch — 3 Speed	3	240	9 7/16	18	11/16